

Healthcare

BRISA®/BRISA® DISTRESSED



303-3914 BARK



303-5747 WHITE




303-3863 CREAM



303-3864 DESERT CLAY



303-3134 BUCKSKIN*



335-3137 SADDLE*




303-3823 AZTEC



303-1373 SALSA



303-9374 BLOSSOM



303-2698 STERLING BLUE



303-2645 CAMBRIDGE BLUE



303-5802 ASH



303-5749 BLACK ONYX

ULTRALEATHER™



291-3851 CHAMOIS



291-5805 ERMINE



291-3609 BUFF



291-1256 PAPRYUS



291-3779 TAUPE



291-2553 CYAN



291-2556 ADMIRAL



291-3777 WALNUT



291-3666 FUDGE



291-1176 RED



291-3469 GARNET



291-5806 SCHOONER



291-5607 RAVEN WING

PROMESSA®




363-4481 SCALLION




363-3152 PARCHMENT



363-3464 TUSK



363-3463 COCOA




363-3462 WOODPECKER



363-5258 SUN SHOWER




363-3145 BRONZE




363-1387 DOGWOOD



363-3037 HORSEHAIR



363-5818 ASH



363-2695 AQUAMARINE



363-2680 ATLANTIC



363-5845 EBONY

VIVA



558-5623 ALUMUNIM



558-3119 BISQUE



558-3324 BALSAM



558-3526 DRIFTWOOD



558-3215 NUBIAN



558-2531 BAHAMAS




558-2652 AZURE



558-2676 PRUSSIAN BLUE



558-4441 ELM



558-8212 LANTERN



558-1322 POINSETTIA



558-9369 CROCUS



558-5600 LAVA

*BRISA® DISTRESSED

SPECIFICATIONS				
	BRISA®/BRISA® DISTRESSED BREATHABLE TECHNOLOGY	ULTRALEATHER™	PROMESSA® ANTIMICROBIAL PROTECTION	VIVA ANTIMICROBIAL PROTECTION
COMPOSITION:	100% POLYURETHANE SURFACE 100% REINFORCED RAYON BACKING	100% POLYURETHANE SURFACE 100% REINFORCED RAYON BACKING	100% POLYURETHANE SURFACE 65% POLYESTER, 35% RAYON BACKING	100% POLYURETHANE SURFACE 65% POLYESTER, 35% RAYON BACKING
WEIGHT:	APPROX. 9.2 OZ. PER SQ. YARD (APPROX. 310 GRAMS PER SQ. METER) APPROX. 13.8 OZ. PER SQ. YARD (APPROX. 430 GRAMS PER SQ. METER)	APPROX. 9.7 OZ. PER SQ. YARD (APPROX. 330 GRAMS PER SQ. METER) APPROX. 14.6 OZ. PER SQ. YARD (APPROX. 450 GRAMS PER SQ. METER)	APPROX. 12 OZ. PER SQ. YARD (APPROX. 410 GRAMS PER SQ. METER) APPROX. 18 OZ. PER SQ. YARD (APPROX. 560 GRAMS PER SQ. METER)	APPROX. 8.8 OZ. PER SQ. YARD (APPROX. 300 GRAMS PER SQ. METER) APPROX. 13.2 OZ. PER SQ. YARD (APPROX. 409 GRAMS PER SQ. METER)
THICKNESS:	APPROX. 1.0 MM	APPROX. 0.95 MM	APPROX. 1.1 MM	APPROX. 1.0 MM
WIDTH:	54" / 137 CM	54" / 137 CM	54" / 137 CM	54" / 137 CM
PUT UP:	APPROX. 33 YRDS / 30 METERS R.O.T.	APPROX. 33 YRDS / 30 METERS R.O.T.	APPROX. 30 YRDS / 27.5 METERS R.O.T.	APPROX. 33 YRDS / 30 METERS R.O.T.
CHARACTERISTICS				
ABRASION: (MEETS OR EXCEEDS)	ASTM D 4157/200,000 DOUBLE RUBS* BS 2543/120,000 RUBS** *WYZENBECK **MARTINDALE	ASTM D 4157/400,000 DOUBLE RUBS* BS 2543/180,000 RUBS** *WYZENBECK **MARTINDALE	ASTM D 4157/400,000 DOUBLE RUBS* BS 2543/180,000 RUBS** *WYZENBECK **MARTINDALE	ASTM D 4157/100,000 DOUBLE RUBS* BS 2543/200,000 RUBS** *WYZENBECK **MARTINDALE
AIR PERMEABILITY:	ASTM D 737	NA	NA	NA
ANTIMICROBIAL:	NA	NA	ASTM E 2180	ASTM E 2180
DIMENSION CHANGE:	ASTM D 3597	ASTM D 3597	ASTM D 3597	ASTM D 3597
HYDROLYSIS:	ASTM D3690-02 SECT. 6.11 (HYDROLIC STABILITY) ISO 1419 METHOD C (ACCELERATED AGEING)	ASTM D3690-02 SECT. 6.11 (HYDROLIC STABILITY) ISO 1419 METHOD C (ACCELERATED AGEING)	ASTM D3690-02 SECT. 6.11 (HYDROLIC STABILITY) ISO 1419 METHOD C (ACCELERATED AGEING)	ASTM D3690-02 SECT. 6.11 (HYDROLIC STABILITY) ISO 1419 METHOD C (ACCELERATED AGEING)
SEAM STRENGTH:	ASTM D 751	ASTM D 751	ASTM D 751	ASTM D 751
STRETCH & SET:	SAE J855	SAE J855	SAE J855	SAE J855
TEAR STRENGTH:	ASTM D 5733	ASTM D 5733	ASTM D 5733	ASTM D 5733
TENSILE STRENGTH:	ASTM D 5034	ASTM D 5034	ASTM D 5034	ASTM D 5034
COLORFASTNESS				
CROCKING:	AATCC 8, CLASS 5 WET & DRY	AATCC 8, CLASS 5 WET & DRY	AATCC 8, CLASS 5 WET & DRY	AATCC 8, CLASS 5 WET & DRY
LIGHT:	AATCC 16E, AATCC 16A, CLASS 4-5 ISO 105 - B02:1999 GRADE 7/8	AATCC 16E, AATCC 16A, CLASS 4-5 ISO 105 - B02:1999 GRADE 7/8	AATCC 16E, AATCC 16A, CLASS 4-5 ISO 105 - B02:1999 GRADE 7/8	AATCC 16E, AATCC 16A, CLASS 4-5 ISO 105 - B02:1999 GRADE 7/8
GAS:	AATCC 23, CLASS 5	AATCC 23, CLASS 5	AATCC 23, CLASS 5	AATCC 23, CLASS 5
OZONE:	AATCC 109, CLASS 5	AATCC 109, CLASS 5	AATCC 109, CLASS 5	AATCC 109, CLASS 5
F/R RATING (HFR FREE)				
F/R RATING:	ASTM E 84 (ADHERED) - CLASS A CA 117 E - CLASS 1 CA TB 117-2013 - PASS FMVSS 302 & 95/28 ANNEX IV - PASS NFPA 260 - CLASS 1 UFAC - CLASS 1	ASTM E 84 (ADHERED) - CLASS A CA 117 E - CLASS 1 CA TB 117-2013 - PASS FMVSS 302 & 95/28 ANNEX IV - PASS NFPA 260 - CLASS 1 UFAC - CLASS 1	ASTM E 84 (ADHERED) - CLASS A CA 117 E - CLASS 1 CA TB 117-2013 - PASS FMVSS 302 & 95/28 ANNEX IV - PASS NFPA 260 - CLASS 1 UFAC - CLASS 1	ASTM E 84 (ADHERED) - CLASS A CA 117 E - CLASS 1 CA TB 117-2013 - PASS FMVSS 302 & 95/28 ANNEX IV - PASS NFPA 260 - CLASS 1 UFAC - CLASS 1

- CAN BE TREATED TO MEET FAR SPECIFICATIONS.
- THESE FABRICS, WHEN TREATED AND/OR USED WITH OTHER COMPATIBLE FURNITURE COMPONENTS, HAVE BEEN SHOWN TO PERFORM WELL UNDER THE FIRE TEST CONDITIONS OF CALIFORNIA TECHNICAL BULLETIN 133, ASTM E 84 (UNADHERED), BS 5852 SOURCE 5 ("CRIBS 5"), BS 7175, BS 5867 PART 2 TYPE B, IMO A.652(16) AND NFPA 701.

MAINTENANCE & CARE INSTRUCTIONS

KEEP ULTRAFABRICS, LLC BRAND SURFACES LOOKING GREAT BY ROUTINE AND PROPER MAINTENANCE. FOLLOW THESE GUIDELINES TO EXTEND THE LIFE OF THE FABRIC:

- Wipe up spills as soon as they occur with soap and water
- Remove stains with alcohol-based cleaners like Fantastik and Formula 409
- Disinfect using a 5:1 water/bleach solution
- Rinse all cleaning solutions with clean water

EARTH FRIENDLY• **GREENGUARD Certified**

- Meets stringent VOC emission standards
- Promotes healthier indoor air quality
- Contributes to LEED and BIFMA level credits
- Compliant with Prop 65
- No Conflict Minerals
- No HFRs (Halogenated Flame Retardants)
- No PBDEs (Polybrominated Diphenyl Ethers)
- Phthalates or Bisphenol A (BPA)
- No POPs (Persistent Organic Pollutants)
- No PVC (Polyvinyl Chloride)
- No toxic by-products
- Over 99% of solvents recaptured and recycled