









Office

FEATURES Meets safety and performance standards of ANSI/BIFMA x 5.1-2002

- Fully upholstered contoured back foam with ergonomically design built in lumbar support
- CFC free molded polyurethane waterfall seat design reduces pressure at the back of the knees allowing for proper blood circulation
- Bicycle T-Arms (UAB) with urethane arm pads, 3" (80mm) height adjustability
- Available with both (TC1) Mechanism with back angle and height adjustment with infinite seat angle adjustment and (MT1) Mechanism with back height and tilt adjustment, seat angle and tilt adjustment with tension knob, forward tilt adjustment, and seat height adjustment
- The seat swivel and height adjustment is obtained by a 4.0" (100mm) pneumatic gas cylinder
- 5-Star, BIFMA approved nylon base
- Casters, (VTW) Carpet-twin wheel casters
- Black finish is standard on mechanism, base and casters



- Adjustable Lumbar Support (ALS)
- Internal back height adjustment (IBC)
- Sliding seat pan (SSP) 3" (80 mm), includes larger base
- Small Seat (3620) (seat width: 18" (460 mm) seat depth: 16.5" (420 mm))
- Medium Seat (3625) (seat width: 19" (480 mm) seat depth: 20" (510 mm))
- Various casters, arm and pneumatic gas cylinder options are available



MAXIMUM H 34.5-39.5" (875-1005 mm) MAXIMUM W 25.5" (650 mm)

MAXIMUM D 27" (685 mm)

SEAT H 18.75-22.75" (475-575 mm)

SEAT W 20.5" (520 mm) SEAT D 19.25" (490 mm) BACK H 25-28" (635-710 mm)

ARM H 25.25-32.25" (640-820 mm)

SHIP WT/CHAIR 43 lbs (19.5 kg) SHIP VOLUME/2 CHAIR 19 ft³ (0.54 m³) COM FABRIC 1.75 yd (1.7 m)
OUANT/CARTON 2











Office

FEATURES Meets safety and performance standards of **ANSI/BIFMA x 5.1-2002**

- Fully upholstered contoured back foam with ergonomically design built in lumbar support
- CFC free molded polyurethane waterfall seat design reduces pressure at the back of the knees allowing for proper blood circulation
- Bicycle T-Arms (UAB) with urethane arm pads, 3" (80mm) height adjustability
- Available with both (TC1) Mechanism with back angle and height adjustment with infinite seat angle adjustment and (MT1) Mechanism with back height and tilt adjustment, seat angle and tilt adjustment with tension knob, forward tilt adjustment, and seat height adjustment
- The seat swivel and height adjustment is obtained by a 4.0" (100mm) pneumatic gas cylinder
- 5-Star, BIFMA approved nylon base
- Casters, (VTW) Carpet-twin wheel casters
- Black finish is standard on mechanism, base and casters

- **OPTIONS** Energy absorbing foam for seat and back (EAFS) (EAFSB)
 - Adjustable Lumbar Support (ALS)
 - Internal back height adjustment (IBC)
 - Sliding seat pan (SSP) 3" (80 mm), includes larger base
 - Small Seat (3620) (seat width: 18" (460 mm) seat depth: 16.5" (420 mm))
 - Medium Seat (3625) (seat width: 19" (480 mm) seat depth: 20" (510 mm))
 - Various casters, arm and pneumatic gas cylinder options are available



MAXIMUM H 42.5-47.5" (1080-1210 mm) MAXIMUM W 25.5" (650 mm)

MAXIMUM D 27" (685 mm)

SEAT H 18.75-22.75" (475-575 mm) **SEAT W** 20.5" (520 mm)

SEAT D 19.25" (490 mm)

BACK H 25-28" (635-710 mm)

ARM H 25.25-32.25" (640-820 mm)

SHIP WT/CHAIR 44 lbs (20 kg) SHIP VOLUME/2 CHAIR 19 ft³ (0.54 m³)

COM FABRIC 2.25 yd (2.1 m) OUANT/CARTON 2













Office

- **FEATURES** Fully upholstered contoured back foam with ergonomically design built in lumbar support
 - CFC free molded polyurethane waterfall seat design reduces pressure at the back of the knees allowing for proper blood circulation
 - Bicycle T-Arms (**UAB**) with urethane arm pads, 3" (80mm) height adjustability
 - Available with (TC1) Mechanism with back angle and height adjustment with infinite seat angle adjustment
 - The seat swivel and height adjustment is obtained by a 10.5" (270mm) pneumatic gas cylinder
 - Height adjustable foot ring
 - 5-Star, BIFMA approved nylon base
 - Casters, (VTW) Carpet-twin wheel casters
 - Black finish is standard on mechanism, base and casters

- **OPTIONS** Energy absorbing foam for seat and back (EAFS) (EAFSB)
 - Adjustable Lumbar Support (ALS)
 - Internal back height adjustment (IBC)
 - Small Seat (3620) (seat width: 18" (460 mm) seat depth: 16.5" (420 mm))
 - Medium Seat (3625) (seat width: 19" (480 mm) seat depth: 20" (510 mm))
 - Various casters, arm and pneumatic gas cylinder options are available



MAXIMUM H 39.5-50" (1005-1270 mm) MAXIMUM W 25.5" (650 mm)

MAXIMUM D 27" (685 mm)

SEAT H 25-35" (635-890 mm) **SEAT W** 20.5" (520 mm)

SEAT D 19.25" (490 mm)

BACK H 19.5-22.5" (495-575 mm)

ARM H 25.25-32.25" (640-820mm)

SHIP WT/CHAIR 43 lbs (19.5 kg) SHIP VOLUME/2 CHAIR 19 ft³ (0.54 m³)

COM FABRIC 1.75 yd (1.7 m) OUANT/CARTON 1

