

Ennis Fabrics

Vinyl **Geoquilt** While every effort is made to present as accurate reproduction as possible, colors on actual products may vary slightly from digital reproductions.



NOTE: We do not guarantee matches and recommend you examine a sample prior to excepting a color match.







ISO 14001 certified





GEOQUILT VINYL

Fabric Card

SPECIFICATIONS		
Contents	100% Vinyl	
Weight	30.96 oz/yd	
Width	54 in. (137 cm)	
Backing	100% Polyester	
Cleaning Code	W	
Eco-Friendly	Eco-Friendly	

PERFORMANCE	
Abraison Resistance* ASTM D-4157	1,500,000 Double Rubs (Wyzenbeek)
UV Resistance	Colorfastness to Light AATCC 16.3 - Grade 4, 1500 hours
Colorfastness to Crocking AATCC 8	AATCC 8: Dry crocking = Class 5
After Treatment Finish	Endurepel Armour - Stain and Soil Resistant, Anti-Bacterial

FLAMMABILITY

CALTB117-2013 IMO FTP 2010 Code MSC.307(88) Part 8 3.1 & 3.2 MVSS302 NFPA 260 Class 1 UFAC Class 1

*This term and any corresponding data refer to typical performance in the specific tests indicated and should not be construed to imply the behavior of this or any other material under actual fire conditions.

This information is offered for your general guidance only. It's accurate to the best of our knowledge and is not intended to relieve the user from its responsibility to investigate and understand other pertinent sources of information to comply with all laws and procedures applicable to the sale handling and use of this material.











