

Vinyl **Turner**

Fabric Card

TURNER VINYL



NOTE: We do not guarantee matches and recommend you examine a sample prior to excepting a color match.



ISO 9001 certified ISO 14001 certified



Borgo Contract Seating 324 Carlingview Drive Toronto, Ontario M9W 5G5 www.borgo.com | sales@borgo.com | T. 416 679.8133 | Toll Free. 1 888 312.6746

© Borgo Contract Seating - December 9, 2020 2:02 PM

TURNER VINYL

SPECIFICATIONS

Content	100% Polyurethane
Backing Content	70% Polyester, 30% Cotton
Abrasion	Exceeds 500,000 Double Rubs
Cold Crack	-40°C (-40°F)
Tear Strength	ASTM D2261: Warp = 20 lbs., Fill = 12 lbs.
Tensile Strength	ASTM D5034: Warp = 105 lbs., Fill = 74 lbs.
UV/Light Fastness	AATCC16 Class 4.5
Elongation	ASTM D5034: Warp = 23.4%, Fill = 38.1%
Fire Retardancy*	CAL 117 - Sec. E, MVSS302, NFPA 260 Class 1,
	UFAC Class 1
Weight	21.18 Ounces per Linear Yard
	14.12 Ounces per Square Yard
Width	54" (137 cm)
Roll Size	30 Yards
Cleaning Instructions	Wipe with a soft cloth, with cold water and a mild soap. Dry immediately.

*This term and any corresponding data refer to typical performance in the specific tests indicated and should not be construed to imply the behavior of this or any other material under actual fire condition. This information is offered for your general guidance only. It's accurate to the best of our knowledge and is not intended to relieve the user from its responsibility to investigate and understand other pertinent sources of information and to comply with all laws and procedures applicable to the safe handling and use of this material. Final determination of the suitability of any product for an application rests with the use.





ISO 9001 certified



Borgo Contract Seating 324 Carlingview Drive Toronto, Ontario M9W 5G5 www.borgo.com | sales@borgo.com | T. 416 679.8133 | Toll Free. 1 888 312.6746