



Madras
Leather Card

MADRAS LEATHER

Leather Card

While every effort is made to present as accurate reproduction as possible, colors on actual products may vary slightly from digital reproductions.



NOTE: We do not guarantee matches and recommend you examine a sample prior to excepting a color match.













MADRAS LEATHER

Leather Card

SPECIFICATIONS

Average Thickness 08-10 mm Tensile Strength min. 10 N/mm 2 Elongation at Break min. 35 % Tear Strength min 40 N Flexing Endurance (20,000 cycles) 20,000 Color Fastness to Artificial Light min. 4 (Blue Scale) Color Fastness to Rubbing (500 Dry Rubs, 100 Wet Rubs) min. 4 (Gray Scale), min. 4 (Gray Scale) Finishing Adhesion min 3 N/cm Determination of pH min 3.2 Ignitability BS 5852-0 (Cigarette) Pass Ignitability BS 5852-1 (Match) Pass Fire & Burning Behavior Cigarette & Match Flame **Pass** California Technical Pass Class 1 Cigarette Ignition Resistance Boston Fire Dept **Pass** Wyzenbeek (70,000 Cycles) Pass













^{*}This term and any corresponding data refer to typical performance in the specific tests indicated and should not be construed to imply the behavior of this or any other material under actual fire condition. This information is offered for your general guidance only. It's accurate to the best of our knowledge and is not intended to relieve the user from its responsibility to investigate and understand other pertinent sources of information and to comply with all laws and procedures applicable to the safe handling and use of this material. Final determination of the suitability of any product for an application rests with the use.